

## DECLARATION OF PERFORMANCE

NO:GRES 01

DRY- PRESSED CERAMIC TILE. WITH WATER ABSORPTION  $E_b \leq 0,5 \%$  FOR  
INTERNAL AND EXTERNAL WALLS AND FLOORINGS

NUOVA RIWAL CERAMICHE SRL, VIA GHIAROLA NUOVA 101  
41042 FIORANO MODENESE (MO) ITALIA

SYSTEM 4

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1 FL/A1	EN 14411:2012
Release of dangerous substance, for:		
_ Cadmium	NPD	
_ Lead	NPD	
Breaking Strenght	>1300 N	
Slipperiness	NPD	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	1N/mm <sup>2</sup>	
Thermal Shock Resistance	PASS	
Durability for:		
_ Internal Use:	PASS	
_ Exetrnal Use: freeze-thaw resistance	PASS	

The performance of the product identified in point 1 is in conformity with the declared performaces in point 6. This declaration of performance is issued under the sole responsibility of the manufacture identified in point 3.

Signed for and on behalf of the manufacturer by :

ALBERTO ALBONETTI  
(Technical Director)

Fiorano Modenese 01/09/2015

## LEISTUNGSKLAERUNG

NO:GRES 01

TROCKENGEPRESSTE KERAMISCHE FLIESEN, MIT WASSERAUFNAHME  $E_b \leq 0,5 \%$   
FUER BODENBELAGE UND WANDBEKLINDUNGEN INNEN UND/ODER AUßEN

NUOVA RIWAL CERAMICHE SRL, VIA GHIAROLA NUOVA, 101  
41042 FIORANO MODENESE (MO) ITALIA

SYSTEM 4

Wesentliche merkmale	Leistung	Harmonisierte technische spezifikation
<b>Brandverhalten</b>	<b>A1 FL/A1</b>	<b>EN 14411:2012</b>
<b>Abgabe gefaehrlicher Substanzen:</b>		
-Kadmiumabgabe	<b>NPD</b>	
-Bleiabgabe	<b>NPD</b>	
<b>Bruchlast (N)</b>	<b>&gt;1300 N</b>	
<b>Rutschhemmende Eigenschaften</b>	<b>NPD</b>	
<b>Taktilitaet</b>	<b>NPD</b>	
<b>Haftfestigkeit:</b>		
Zementkleber, type C2	<b>1N/mm2</b>	
<b>Temperaturwechselbestaendigkeit</b>	<b>BESTANDEN</b>	
<b>Dauerhaftigkeit:</b>		
_ Innenbereichen:	<b>BESTANDEN</b>	
_ Aussenbereichen:	<b>BESTANDEN</b>	
Frost-Tau. Wechselbestaendigkeit		

Die Leistung der im Absatz 1 identifizierten Leistungen entsprechen den Leistungen des Absatzes 6.  
Diese Leistungserklaerung wird gemäss der Verordnung (EU) Nr.305/2011 unter der alleinigen  
Verantwortung des in nummer 3 genannten Herstellers ausgestellt.

Unterzeichnet in namen und im auftrag der hersteller von:

ALBERTO ALBONETTI  
(Technical Director)

Fiorano Modenese 01/09/2015

## DECLARATION OF PERFORMANCE

NO: GRES +

DRY- PRESSED CERAMIC TILE. WITH WATER ABSORPTION  $E_b \leq 0,5 \%$  FOR FLOOR  
INTERNAL AND EXTERNAL

NUOVA RIWAL CERAMICHE SRL, VIA GHIAROLA NUOVA 101  
41042 FIORANO MODENESE (MO) ITALIA

SYSTEM 4

Essential Characteristics	Performance	Harmonised Technical Specification
<b>Reaction to fire</b>	<b>A1 FL/A1</b>	<b>EN 14411:2012</b>
<b>Release of dangerous substance, for:</b>		
_ Cadmium	<b>NPD</b>	
_ Lead	<b>NPD</b>	
<b>Breaking Strenght</b>	<b>&gt;700 N</b>	
<b>Slipperiness</b>	<b>NPD</b>	
<b>Tactility</b>	<b>NPD</b>	
<b>Bond strength/adhesion, for:</b>		
Cementitious adhesive, type C2	<b>1N/mm<sup>2</sup></b>	
<b>Thermal Shock Resistance</b>	<b>PASS</b>	
<b>Durability for:</b>		
_ Internal Use:	<b>PASS</b>	
_ Exetrnal Use: freeze-thaw resistance	<b>PASS</b>	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacture identified in point 3.

Signed for and on behalf of the manufacturer by :

ALBERTO ALBONETTI  
(Technical Director)

Fiorano Modenese 01/02/2018